

**(Document Version 1.4)**

(This Document gives details on how to send messages via the Bulk HTTP API for the Route Mobile SMPP System)

## HTTP SSL API to submit messages on SMPP:

**Error! Hyperlink reference not valid.>**

<server>: sms6.routesms.com

<port>: 8443

Parameters are explained below, please note that all the parameters (especially message and url) should be URL-UTF-8 encoded.

**username:** User name of the SMPP Account

**password:** Password of the SMPP Account

**type:** Indicates the type of message.

Values for "**type**":-

- 0: Plain Text (GSM 3.38 Character encoding)
- 1: Flash Message (GSM 3.38 Character encoding)
- 2: Unicode
- 3: Reserved
- 4: WAP Push
- 5: Plain Text (ISO-8859-1 Character encoding)
- 6: Unicode Flash
- 7: Flash Message (ISO-8859-1 Character encoding)

**dlr:** Indicates whether the client wants delivery report for this message

Range of values for "**dlr**":-

- 0: No Delivery report required
- 1: Delivery report required

**destination:** Mobile Number to which to Send message to (may or may not include a '+' sign), multiple mobile numbers can be separated by commas (note the comma (',') should be URL encoded).

**source:** The sender address that should appear in the message

Max Length of 18 if Only Numeric

Max Length of 11 if Alpha numeric

If you wish plus ('+') should be prefixed to the sender address when the message is displayed on the cell phone, please prefix the plus sign to your sender address while submitting the message (note the plus

sign should be URL encoded). Additional restrictions on this field may be enforced by the SMSC.

**message:** The message to send (Can be used for 'long' messages, that is, messages longer than 160 characters for plain text, 160 for flash and 280 for Unicode) For concatenated (long) messages we will be counting as one message for every 153 characters for plain text and 268 characters for Unicode, as the rest of the characters will be used by the system for packing extra information for re-assembling the message on the cell phone.

In case of WAP Push (type = 4), this is the text that would appear in the message. Also in the latter case, to send non-English characters in the message, you only have to directly URL encode them (using UTF-8 character encoding scheme).

**url:** If sending a WAP Push message (type=4), this holds the link that you wish to send, for any other type of message, no value needs to be supplied for this field (if specified will be ignored) . Just like "message" field, this field should also be URL encoded with UTF-8 character encoding (even for sending non-ASCII domain names).

#### Error Codes:

- **Success**, Message Submitted Successfully, In this case you will receive the response  
**1701|<CELL\_NO>:<MESSAGEID>:<COUNTRY>:<OPERATOR>:<TOTAL\_MSG\_CHUNKS>:<COST\_PER\_SMS>:<TOTAL\_CHARGE\_DEDUCTED>**, The message Id can then be used later to map the delivery reports to this message. Name of the Country to which destination is mapped to else Country will be set as UNKNOWN. Operator Name to which destination is mapped to else Operator will be set as UNKNOWN. Total Message chunk or total message count of the submitted message. Cost Per Sms of the submitted message for 1 message count or 1 message chunk. Total Charge that is deducted depending on the total message chunk or total message count of the submitted message.
- Invalid URL Error, This means that **one of the parameters was not provided** or left blank
- Invalid value in **username** or **password** field
- Invalid value in "**type**" field
- Invalid **Message**
- Invalid **Destination**

- Invalid **Source** (Sender)
- Invalid value for "**dlr**" field
- **User validation failed**
- Internal Error
- **:Insufficient Credit**

**Note:-**

- Along with the above errors codes, standard SMPP v3.4 error codes may also be returned where applicable.
- **Apart from 1709, Please DO NOT RETRY re-sending the message for any other error code (including SMPP v3.4 Error codes ).**
- While sending messages with type=0 there are some special characters which end up taking the space of more than one character after final encoding and while sending to the SMSC. The following is the list of such known characters:-

Characte r	Character	GSM 03.38
^	Circumflex Accent	0x1B14
{	Left Curly Bracket	0x1B28
}	Right Curly Bracket	0x1B29
\	Reverse Solidus (Backslash)	0x1B2F
[	Left Square Bracket	0x1B3C
~	Tilde	0x1B3D
]	Right Square Bracket	0x1B3E
	Vertical Bar	0x1B40
€	Euro Sign	0x1B65

Please do note that the above list is not exhaustive and hence before sending any special characters do test to see if they are supported.

**Important information about WAP Push:-**

- WAP Push messages are sent in binary mode and hence only one hundred and forty, eight bit characters (octets) are allowed in a single message, also due to the nature of the message approximately thirty two characters are used to pack the document encoding standards so that the phone recognizes the message correctly. As a result only

approximately one hundred and eight characters are available to send in each message (URL + message to display). However if your URL contains some common patterns they are encoded to occupy less space as shown below:-

Pattern	Length	Actual Length
<a href="#">http://</a>	7	1
<a href="#">http://www.</a>	11	1
<a href="#">https://</a>	8	1
<a href="#">https://www</a>	12	1
.		
.com/ .edu/ .net/ .org/	4	1 [ if at the end of the link eg: <a href="#">http://www.routemobile.com/</a> ] 3 [ if in the link, eg: <a href="#">http://www.routemobile.com/bulksms</a> ]

Apart from the exceptions in the previous table, all other characters are encoded using the UTF-8 character encoding, thus expanding the range of characters supported in a WAP Push (both "message" and "url"). Please refer to the home page of the [Unicode Consortium](#) for more details like list of supported characters and how many octets a specified character would consume as per the UTF-8 encoding scheme.

- Long WAP Push messages:** If the total message length after encoding the document encoding standards with the message text and the URL exceed one hundred and forty octets, your account will automatically be charged the excess credits. For WAP Push messages longer than one hundred and forty octets, the number of octets usable for the message text and URL in each message part is further reduced from approximately one hundred and eight to one hundred and three only.



## Bulk SMS API Reply Format:

```
<Error_Code>|<destination>:<message_id>:<country>:<operator>:<total  
_msg_chunks>:<cost_per_sms>:<total_charge_deducted>,<Error_Code>|  
<destination>:<message_id>...
```

## Exceptional Situations:-

A request containing multiple destinations will be aborted immediately if any error other than "Invalid Destination" is found, in case an invalid destination is found we just skip that destination and proceed to the next destination.

If while processing the request the SMPP Server goes down, the HTTP API will retry a fixed number (with a gap of ten milliseconds between consecutive retries) of times to reconnect to the SMPP server and submit the message. In case the SMPP server does not come up before the fixed number of attempts are exhausted, the batch will be aborted at that destination and a message will be returned in following format:-

```
<Error_Code>|<destination>:<message_id>:<country>:<operator>:<total  
_msg_chunks>:<cost_per_sms>:<total_charge_deducted>,1709|<destinati  
on_at_which_batch_aborted>
```

The third and final situation which can arise is the the credits can get exhausted in the middle of a request being serviced. In case such a situation occurs we will be aborting the batch on the destination at which we got the "Insufficient\_Credit" error, and a response in the following format will be returned to the client:-

```
<Error_Code>|<destination>:<message_id>:<country>:<operator>:<total  
_msg_chunks>:<cost_per_sms>:<total_charge_deducted>,1025|<destinati  
on_at_which_batch_aborted>
```

### **Example Link to Submit Plain Text Messages (GSM 03.38 character set):**

#### **Error! Hyperlink reference not valid.!!!**

The following observations can be made in the above URL:-

- 'type=0', indicates this is a message of type plain text, this mode supports all characters falling under the GSM 03.38 character set.
- 'dlr=1', indicates delivery report for this message is enabled.
- 'message=Demo%20Message!!!', The message field contains the content to send in an URL encoded format, on using the appropriate username and password in the above link you will get the 'Demo Message!!!' on your mobile phone.
- 'destination=%2B919818181', An optional plus is included in the destination field here, Do note that the '+' sign is URL encoded.

### **Example Link to Submit Plain Text Messages (ISO-8859-1 Character set):**

#### **Error! Hyperlink reference not valid.!!!**

The following observations can be made in the above URL:-

- 'type=5', indicates message is of type plain text, this mode supports all characters falling under the ISO-8859-1 character set.
- 'dlr=0', indicates delivery report for this message is not enabled.
- 'message=Demo%20Message!!!', the message field contains the message to send in an URL encoded format, on using the appropriate username and password in the above link you will get the message "Demo Message!!!" on your mobile phone.
- 'destination=919818181', the optional '+' has been omitted.

### **Example Link to Submit Flash Messages (GSM 03.38 Character set):**

#### **Error! Hyperlink reference not valid.!!!**

On calling the above link by replacing the username and password by your account username and password, the message 'Demo Message!!!' should display on your cell phone.

The characters in the message field should fall in the GSM 03.38 character set and the type parameter has to be set to 1 i. e. (type=1).

### **Example Link to Submit Unicode Flash Messages :**

#### **Error! Hyperlink reference not valid.**

On calling the above link by replacing the username and password by your account username and password, the sms 'Demo Message!!!' should flash on the mobile no in the destination field.

The message has to be encoded in the UTF-16BE format and the type parameter has to be set to 6 i.e. (type=6).

### **Example Link to Submit Unicode Messages :**

#### **Error! Hyperlink reference not valid.**

On calling the above link by replacing the username and password by your account username and password, you should get the sms 'Demo Message!!!' on the mobile no in the destination field.

The message has to be encoded on the UTF-16BE format and the type parameter has to be set to 6 i.e. (type=2).

### **Example Link to Submit WAP Push Messages:**

#### **Error! Hyperlink reference not valid.**

The following observations can be made in the above URL:-

- 'type=4', indicates this is a WAP Push, this mode supports all characters falling under the Unicode character set both in 'message' field and 'url'.
- 'dlr=1', indicates delivery report for this message is needed.
- 'message=Test%20WAP%20Push%20Special%20Characters%3A%20%C2%B6%C2%BE%20Arabic%3A%20%D8%A6%20Greek%3A%20%CD%BC!!!', The message field contained the message to displayed in URL encoded format, on using the appropriate username and password in the above link you will get a service message with text, 'Test WAP Push Special Characters: ¶¾ Arabic: ء Greek: eht no ,c :sserdda bew eht ot deknil repyh ,enohp llec deificeps  
</moc.elibometuor.www//:ptth>
- 'url=http%3A%2F%2Fwww.routemobile.com%2F', URL Encoded format of '<http://www.routemobile.com/>'



## Appendix

### GSM 03.38 Character set

<b>GSM 03.38</b>																
	<b>x0</b>	<b>x1</b>	<b>x2</b>	<b>x3</b>	<b>x4</b>	<b>x5</b>	<b>x6</b>	<b>x7</b>	<b>x8</b>	<b>x9</b>	<b>xA</b>	<b>xB</b>	<b>xC</b>	<b>xD</b>	<b>xE</b>	<b>xF</b>
<b>0x</b>	@	£	\$	¥	è	é	ù	ì	ò	Ç	LF	∅	ø	CR	Å	å
<b>1x</b>	Δ	_	Φ	Γ	Λ	Ω	Π	Ψ	Σ	Θ	≡	ESC	Æ	æ	β	É
<b>2x</b>	SP	!	"	#	α	%	&	'	(	)	*	+	,	-	.	/
<b>3x</b>	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
<b>4x</b>	i	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
<b>5x</b>	P	Q	R	S	T	U	V	W	X	Y	Z	Ä	Ö	Ñ	Ü	§
<b>6x</b>	ç	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
<b>7x</b>	p	q	r	s	t	u	v	w	x	y	z	ä	ö	ñ	ü	à
<b>1B 0x</b>												FF				
<b>1B 1x</b>					^											
<b>1B 2x</b>									{	}						\
<b>1B 3x</b>													[	~	]	
<b>1B 4x</b>																
<b>1B 5x</b>																
<b>1B 6x</b>						€										
<b>1B 7x</b>																

## ISO-8859-1 Character set

ISO/IEC 8859-1																
	x0	x1	x2	x3	x4	x5	x6	x7	x8	x9	xA	xB	xC	xD	xE	xF
0	unused															
1	unused															
2x	SP	!	"	#	\$	%	&	'	(	)	*	+	,	-	.	/
3x	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
4x	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
5x	P	Q	R	S	T	U	V	W	X	Y	Z	[	\	]	^	_
6x	`	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
7x	p	q	r	s	t	u	v	w	x	y	z	{		}	~	
8	unused															
9	unused															
Ax	NBSP	ı	¢	£	¤	¥	¦	§	¨	©	ª	«	¬	SHY	®	¯
Bx	°	±	²	³	´	µ	¶	·	¸	¹	º	»	¼	½	¾	¿
Cx	À	Á	Â	Ã	Ä	Å	Æ	Ç	È	É	Ê	Ë	Ì	Í	Î	Ï
Dx	Ð	Ñ	Ò	Ó	Ô	Õ	Ö	×	Ø	Ù	Ú	Û	Ü	Ý	Þ	ß
Ex	à	á	â	ã	ä	å	æ	ç	è	é	ê	ë	ì	í	î	ï
Fx	ð	ñ	ò	ó	ô	õ	ö	÷	ø	ù	ú	û	ü	ý	þ	ÿ

Code values 00–1F, 7F, and 80–9F are not assigned to characters by ISO/IEC 8859-1.

## Calling HTTP API Using .Net

```
Imports System.IO
Imports System.Net
Imports System.Data
Partial Class SendUsingSMPP
Inherits System.Web.UI.Page
Protected Sub Page_Load(ByVal sender As Object, ByVal e As
System.EventArgs) Handles Me.Load
Dim WebRequest As Net.WebRequest 'object for WebRequest
Dim WebResonse As Net.WebResponse 'object for WebResponse
'.....

' DEFINE PARAMETERS USED IN URL
'.....

'To what server you need to connect to for submission
'i.e. Dim Server As String = "smpp1.spheredge.com"
Dim Server As String = ""
'Port that is to be used like 8080 or 8000
Dim Port As String = ""
'Username that is to be used for submission
'i.e. Dim UserName As String = "tester"
Dim UserName As String = ""
' password that is to be used along with username
'i.e. Dim Password As String = "password"
Dim Password As String = ""
'What type of the message that is to be sent.
'0:means plain text
'1:means flash
'2:means Unicode (Message content should be in Hex)
'6:means Unicode Flash(Message content should be in Hex)
Dim type As Integer = 0
'Message content that is to be transmitted
Dim Message As String = "Test Message"
'Url Encode message
Message = HttpUtility.UrlEncode(Message)
If (Message = 2) Or (Message = 6) Then
    Message = ConvertToUnicode(Message)
End If
'Require DLR or not
'0:means DLR is not Required
```

```

'1:means DLR is Required
Dim DLR As Integer = 1
'Sender Id to be used for submitting the message
'i.e. Dim SenderName As String = "test"
Dim Source As String = ""
'Destinations to which message is to be sent For submitting more
than one
'destination at once destinations should be comma separated Like
'91999000123,91999000124
Dim Destination As String = ""
""""CODE COMPLETE TO DEFINE PARAMETER""""
Dim WebResponseString As String = ""
Dim URL As String = "https://" & Server & ":" & Port &
"/bulksms/bulkpush?username=" & UserName & "&password=" &
Password & "&type=" &
type & "&dlr=" & DLR & "&destination=" & Destination & "&source="
&Source & "&message=" & Message & ""
WebRequest = Net.HttpWebRequest.Create(URL) 'Hit URL Link
WebRequest.Timeout = 25000
Try
    WebResonse = WebRequest.GetResponse 'Get Response
    Dim reader As IO.StreamReader = New
    IO.StreamReader(WebResonse.GetResponseStream)
    'Read Response and store in variable
    WebResponseString = reader.ReadToEnd()
    WebResonse.Close()
    Response.Write(WebResponseString) 'Display Response.
Catch ex As Exception
    WebResponseString = "Request Timeout" 'If any exception
    occur.
    Response.Write(WebResponseString)
End Try
End Sub
'Function To Convert String to Unicode if MessageType=2 and 6.
Public Function ConvertToUnicode(ByVal str As String) As String
Dim ArrayOFBytes() As Byte =
System.Text.Encoding.Unicode.GetBytes(str)
Dim UnicodeString As String = ""
Dim v As Integer
For v = 0 To ArrayOFBytes.Length - 1

```

```
If v Mod 2 = 0 Then
    Dim t As Integer = ArrayOFBytes(v)
    ArrayOFBytes(v) = ArrayOFBytes(v + 1)
    ArrayOFBytes(v + 1) = t
End If
Next
For v = 0 To ArrayOFBytes.Length - 1
    Dim c As String = Hex$(ArrayOFBytes(v))
    If c.Length = 1 Then
        c = "0" & c
    End If
    UnicodeString = UnicodeString & c
Next
Return UnicodeString
End Function
End Class
```

Calling HTTP API Using php

```
<?php
class Sender{
    var $host;
    var $port;
    /*
    * Username that is to be used for submission
    */
    var $strUserName;

    /*
    * password that is to be used along with username
    */
    var $strPassword;

    /*
    * Sender Id to be used for submitting the message
    */
    var $strSender;

    /*
    * Message content that is to be transmitted
```



```

*/
var $strMessage;

/*
* Mobile No is to be transmitted.
*/
var $strMobile;

/*
* What type of the message that is to be sent
* <ul>
* <li>0:means plain text</li>
* <li>1:means flash</li>
* <li>2:means Unicode (Message content should be in
Hex)</li>
* <li>6:means Unicode Flash (Message content should be in
Hex)</li>
* </ul>
*/
var $strMessageType;

/*
* Require DLR or not
* <ul>
* <li>0:means DLR is not Required</li>
* <li>1:means DLR is Required</li>
* </ul>
*/
var $strDlr;

private function sms__unicode($message){
    $hex1="";
    if (function_exists('iconv')) {
        $latin = @iconv('UTF-8', 'ISO-8859-1', $message);
        if (strcmp($latin, $message)) {
            $arr = unpack('H*hex', @iconv('UTF-8', 'UCS-
                2BE', $message));
            $hex1 = strtoupper($arr['hex']);
        }
        if($hex1 == ""){

```

```

        $hex2="";
        $hex="";
        for ($i=0; $i < strlen($message); $i++){
            $hex = dechex(ord($message[$i]));
            $len =strlen($hex);
            $add = 4 - $len;
            if($len < 4){
                for($j=0;$j<$add;$j++){
                    $hex="0".$hex;
                }
            }
            $hex2.=$hex;
        }
        return $hex2;
    }
    else{
        return $hex1;
    }
}
else{
    print 'iconv Function Not Exists !';
}
}

//Constructor..
public function Sender
($host,$port,$username,$password,$sender,$message,$mobile,$msgtype,$
dlr){
    $this->host=$host;
    $this->port=$port;
    $this->strUserName = $username;
    $this->strPassword = $password;
    $this->strSender= $sender;
    $this->strMessage=$message; //URL Encode The
Message..
    $this->strMobile=$mobile;
    $this->strMessageType=$msgtype;
    $this->strDlr=$dlr;
}

```

```

public function Submit(){
    if($this->strMessageType=="2" ||
        $this->strMessageType=="6") {

        $this->strMessage = $this->sms__unicode(
            $this->strMessage);
            //Call The Function Of String To HEX.
        echo $this->strMessage;
        exit;
    }
    else
        $this->strMessage=urlencode($this->strMessage);
    try{
        //Smpp http Url to send sms.
        $live_url="https://".$this->host.":".$this-
>port."/bulkpush?username=".$this->strUserName."&password=".$this-
>strPassword."&type=".$this->strMessageType."&dlr=".$this-
>strDlr."&destination=".$this->strMobile."&source=".$this-
>strSender."&message=".$this->strMessage."";

        $parse_url=file($live_url);
        echo $parse_url[0];
    }
    catch(Exception $e){
        echo 'Message:' .$e->getMessage();
    }
}

//Call The Constructor.
$obj = new
Sender("IP","Port","","","Tester","العربية","919990001245"
    ,"2","1");
$obj->Submit ();
?>

```

## Calling HTTP API Using Java

```

import java.io.BufferedReader;
import java.io.DataOutputStream;
import java.io.InputStreamReader;
import java.net.HttpURLConnection;
import java.net.URL;
import java.net.URLEncoder;

/**
 * An Example Class to use for the submission using HTTP API You can
perform
 * your own validations into this Class For username,
password,destination,
 * source, dlr, type, message, server and port
 */

public class Sender {

    // Username that is to be used for submission
    String username;
    // password that is to be used along with username
    String password;
    // Message content that is to be transmitted
    String message;

    /**
     * What type of the message that is to be sent
     * <ul>
     * <li>0:means plain text</li>
     * <li>1:means flash</li>
     * <li>2:means Unicode (Message content should be in
Hex)</li>
     * <li>6:means Unicode Flash (Message content should be in
Hex)</li>
     * </ul>
     */
    String type;

    /**

```

```

* Require DLR or not
* <ul>
* <li>0:means DLR is not Required</li>
* <li>1:means DLR is Required</li>
* </ul>
*/

```

```
String dlr;
```

```
/**
```

\* Destinations to which message is to be sent For submitting

more than one

```
* destination at once destinations should be comma separated
```

Like

```
* 91999000123,91999000124
```

```
*/
```

```
String destination;
```

```
// Sender Id to be used for submitting the message
```

```
String source;
```

```
// To what server you need to connect to for submission
```

```
String server;
```

```
// Port that is to be used like 8080 or 8000
```

```
int port;
```

**public** Sender(String server, **int** port, String username, String password,

```
String message, String dlr, String type, String destination,
String source) {
```

```
this.username = username;
```

```
this.password = password;
```

```
this.message = message;
```

```
this.dlr = dlr;
```

```
this.type = type;
```

```
this.destination = destination;
```

```
this.source = source;
```

```
this.server = server;
```

```
this.port = port;
```

```
}
```



```

private void submitMessage() {
    try {
        // Url that will be called to submit the message
        URL sendUrl = new URL("http://" + this.server +
        ":" + this.port
            + "/bulksms/bulkpush");

        HttpURLConnection httpConnection =
        (HttpURLConnection) sendUrl
            .openConnection();

        // This method sets the method type to POST so that
        // will be send as a POST request
        httpConnection.setRequestMethod("POST");
        // This method is set as true wince we intend to send
        // input to the server
        httpConnection.setDoInput(true);
        // This method implies that we intend to receive data
        from server.

        httpConnection.setDoOutput(true);

        // Implies do not use cached data
        httpConnection.setUseCaches(false);

        // Data that will be sent over the stream to the
        server.

        DataOutputStream dataStreamToServer = new
        DataOutputStream(
            httpConnection.getOutputStream());
        dataStreamToServer.writeBytes("username="
            + URLEncoder.encode(this.username, "UTF-
            8") + "&password="
            + URLEncoder.encode(this.password, "UTF-8")
            + "&type="
            + URLEncoder.encode(this.type, "UTF-8") +
            "&dlr="
            + URLEncoder.encode(this.dlr, "UTF-8") +
            "&destination="
  
```

```

8") + "&source="
"&message="
8"));

```

```

+ URLEncoder.encode(this.destination, "UTF-
+ URLEncoder.encode(this.source, "UTF-8") +
+ URLEncoder.encode(this.message, "UTF-

```

```

dataStreamToServer.flush();
dataStreamToServer.close();

```

```

// Here take the output value of the server.
BufferedReader dataStreamFromUrl = new

```

```

BufferedReader(

```

```

    new

```

```

InputStreamReader(httpConnection.getInputStream()));

```

```

String dataFromUrl = "", dataBuffer = "";

```

```

// Writing information from the stream to the buffer

```

```

while ((dataBuffer =
dataStreamFromUrl.readLine()) != null) {
    dataFromUrl += dataBuffer;
}

```

```

/**

```

received from the

```

* Now dataFromUrl variable contains the Response

```

it accordingly.

```

* server so we can parse the response and process

```

```

*/

```

```

dataStreamFromUrl.close();

```

```

System.out.println("Response: " + dataFromUrl);

```

```

} catch (Exception ex) {
    ex.printStackTrace();
}

```

```

}
}

```

```

public static void main(String[] args) {

```

```

    try {

```

```

        // Below exmaple is for sending Plain text

```

```

Sender s = new Sender("server", 8080, "xxxx",
    "xxxx", "test for unicode", "1", "0",
    "440000xxx",
    "Update");
s.submitMessage();
// Below example is for sending unicode
Sender s1 = new Sender("server", 8080, "xxxx",
    "xxx", convertToUnicode("test for
unicode").toString(),
    "1", "2", "44000xx", "Update");
s1.submitMessage();
} catch (Exception ex) {
}
}

/**
 * Below method converts the unicode to hex value
 * @param regText
 * @return
 */
private static StringBuffer convertToUnicode(String regText) {

    char[] chars = regText.toCharArray();
    StringBuffer hexString = new StringBuffer();
    for (int i = 0; i < chars.length; i++) {

        String iniHexString = Integer.toHexString((int)
chars[i]);

        if (iniHexString.length() == 1)
            iniHexString = "000" + iniHexString;
        else if (iniHexString.length() == 2)
            iniHexString = "00" + iniHexString;
        else if (iniHexString.length() == 3)
            iniHexString = "0" + iniHexString;

        hexString.append(iniHexString);
    }
    System.out.println(hexString);
    return hexString;
}

```

}  
}